## OpenBSD MAC(B) Timestamps

М	Last data Modification				
A	Last data Access				
С	Last file status Change				
В	Birth: not used (always 0)				
Resolution	1 nanosecond				
M/A/C	M/A/C is updated to current time				
m/a/c	M/A/C is inherited from m/a/c of source file/dir				
	M/A/C is not modified				

Mount Option	Description
(default)	MAC updates are all performed
noatime	A updates are performed only if M or C is also marked for update

	New File/Dir	File Read /Execute	Symlink Read/Follow	File Write	File/Dir Change	New/Delete Hardlink	File/Dir Rename	Local File Move	Local Dir Move	Volume File/Dir Move	File/Dir Copy (new)	File Copy (existing)
	touch, mkdir	cat, exec()	readlink	>, >>	chmod, chown	ln, rm	mv	mv	mv	ср	ср	
M	M	•	•	M	•	•	•	•	M	m	M	M
A	A	A	•	•	•	•	•	•	•	a	A	•
С	С	•	•	С	С	С	С	С	С	С	С	С

	<b>Dir</b> Traversal			<b>Dir</b> : New/Rename Child (File/Dir/Hardlink)	<b>Dir</b> : Delete Child (File/Dir/Hardlink)	<b>Dir</b> : Child Read/Exec/Write/Change		
	cd	ls	m∨	touch, mkdir, ln, mv, cp	rm, mv	cat, readlink, >>		
M	•		M	M	M	•		
A	•	A	A	•	•	•		
С	•		С	С	С	•		

QuoScient, 2019-12-03

Tested against FFS1 on OpenBSD 65